



## Quick-Reference Application Guide

(IMPORTANT: The quick reference guide must be used with the full set of Application Instructions included in each package of TopMark® materials)

### General

- Contact Flint Trading Inc. for training if you are a first time applicator.
- Apply when ambient temperature is 45°F and rising.
- Prepare surface: clean, remove moisture, check porosity.
- Contact Flint Trading for application over asphalt, joints, cuts, imprints or grooves.

### Safety Precautions

- Read MSDS before proceeding.
- Wear work shoes, long pants, safety glasses and gloves (provided).
- Avoid skin contact with sealer/bonder paste.
- **Do not** allow sealer/bonder paste to puddle up.

### Sealer

- Lay out material on ramp and mark outline with marker (provided).
- After loading sealer cartridge into gun dispense onto surface.
- Using foam roller (provided), roll approximately ½” beyond marked outline.

### Bonder Paste

- Keep bonder paste warm during application.
- After loading bonder paste cartridge into gun dispense onto surface.
- Using foam roller (provided), push (rather than roll) bonder paste.
- **Do not** apply bonder paste beyond marked outline.

### Domed Sheets

- Immediately hand-tack edges of domed sheets onto application area.
- Check for excess squeeze out. Add more bonder paste if necessary.
- Clean any excess bonder paste using wood scraper and paper towel.

### Heat & Roll

- Heat 4 sq ft area of domed sheets to temperature range of 215°F - 250°F.
- Place holed corrugated package inserts on heated domed sheet.
- Using 35 lb segmented roller, roll the domed area covered by inserts.
- Roll uphill and away from you then back to edge nearest you.
- Remove inserts (**Do not re-use holed corrugated inserts**).
- Continue alternately heating and rolling until complete.

### Finish

- Clean any excess bonder paste using wood scraper and paper towel.
- Heat the edges of the entire installation directing flame away from domes.
- Set cones around application. Wait 30-45 minutes before allowing traffic.

### Tools



Flint 2000EX  
Propane Torch



Sealer & Bonder  
Paste Guns



Infrared thermometer



TopMark® 35 lb roller